



3108A Paired - EIA Industrial RS-485 PLTC/CM

 	<p>Metric Version For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

22 AWG stranded (7x30) tinned copper conductors, Datalene® insulation, twisted pairs, overall Beldfoil® shield (100% coverage) plus a tinned copper braid (90% coverage), drain wire, UV resistant PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	3
Total Number of Conductors	6
AWG	22
Stranding	7x30
Conductor Diameter	0.762 mm
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material Trade Name	Datalene®
Insulation Material	FHDPE - Foam High Density Polyethylene

OVERALL CABLING:

Overall Cabling Color Code Chart :

Number	Color
1	White/Blue Stripe & Blue/White Stripe
2	White/Orange Stripe & Orange/White Stripe
3	White/Green Stripe & Green/White Stripe

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	90

Outer Shield %Coverage	100 %
------------------------	-------



3108A Paired - EIA Industrial RS-485 PLTC/CM

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	7x30
Outer Shield Drain Wire Diameter	0.762 mm
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	10.668 mm
--------------------------	-----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +60°C
Non-UL Temperature Rating	60°C
Bulk Cable Weight	126.497 Kg/Km
Max. Recommended Pulling Tension	400.338 N
Min. Bend Radius (Install)	107.95 mm

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM, PLTC OIL RES II
CEC/C(UL) Specification	CM
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005

FLAME TEST:

UL Flame Test	UL1685 UL Loading
CSA Flame Test	FT1

SUITABILITY:

Sunlight Resistance	Passes UL 1581, 720 Hours
---------------------	---------------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Input/Unfitted Impedance :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Input/Unfitted Impedance (Ohms)
	1			

Nom. Characteristic Impedance	120 Ohms
-------------------------------	----------

Nom. Capacitance Conductor to Conductor @ 1 KHz	36.091 pF/m
---	-------------



3108A Paired - EIA Industrial RS-485 PLTC/CM

Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	68.573 pF/m
Nominal Velocity of Propagation	78 %
Nom. Conductor DC Resistance @ 20 Deg. C	48.231 Ohms/km
Nominal Outer Shield DC Resistance @ 20 Deg. C	4.922 Ohms/km

Nom. Attenuation (dB/100 ft) :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100m)
	1			1.64

Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	2.7 Amps per conductor @ 25°C

NOTES:

Notes	Oil Resistance: Passes Oil Res II Per UL1277, Table 10.17. For CPE jacketed version order YR45287.
-------	--

PUT-UPS AND COLORS:

Item	Description	Put-Up (M)	Ship Weight (kgs.)	Jacket Color	Notes
3108A 0101000	3 PR #22 FHDPE SH PVC	304.8	42.222	BLACK	C
3108A 0102000	00PR #22 FHDPE SH PVC	609.6	83.536	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 10-10-2005

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.